



drivers

LED DRIVERS in corrente continua
LED DRIVERS constant current**0127****LED driver**
IN: 100 - 240V
OUT: 500mA
1-6 Power LED

11,6 x 3,4 x 2 cm 4 cm




SELV CLASS 2


0169/50**Multipower LED driver**IN: 220 - 240V
OUT: 500mA
4-15 Power LED

13 x 7,5 x 3 cm 8,5 cm


SELV

DRIVERS DIMMERABILI in corrente continua
DIMMABLE LED DRIVERS constant current**0129 Dimmer LED****Multipower dimmable driver**IN: 110 - 240V
OUT: 500mA,
1-14 Power LED


10,5 x 7 x 2,2 cm 7,2 cm SELV

0129/DALI Dimmer LED**Multipower dimmable driver**IN: 110 - 240V
OUT: 500mA
2-12 Power LED

10,5 x 7 x 2,2 cm 7,2 cm SELV


0141/DALI**LED driver**IN: 110 - 240V
OUT: 500mA,
1-11 Power LED

11,1 x 5,2 x 2,5 cm 5,5 cm


0141/DIM**LED driver**IN: 110 - 240V
OUT: 500mA,
1-11 Power LED

Versione PUSH non sincronizzabile - PUSH version not synchronizable

11,1 x 5,2 x 2,5 cm 5,5 cm

0145 Dimmer LED Maxi**Multipower dimmable driver**IN: 110 - 240V
OUT: 500mA,
1- 21 Power LED

12,3 x 8 x 2,2 cm 8,4 cm SELV


0145/DALI Dimmer LED Maxi**Multipower dimmable driver**IN: 110 - 240V
OUT: 500mA,
1- 21 Power LED

12,3 x 8 x 2,2 cm

8,4 cm SELV


0133Cavo di sincronizzazione per dimmer LED
Synchronization cable for LED dimmers
(art. 0129 - art. 0129/DALI - art. 0145 - art. 0145/DALI)

L 150 cm

IP LED DRIVERS in corrente continua
IP LED DRIVERS constant current**0143/IP****LED driver**
IN: 220 - 240V
OUT: 500mA
1-7 Power LED

8,2 x 3,9 x 2 cm 4,5 cm

SELV IP67

EGOLUCE s.r.l., via I. Newton 12 - 20016 Pero - Milano
telefono +39 02 339586.1 - fax. +39 02 3535112
e-mail: info@egoluce.com - http://www.egoluce.com