


drivers

LED DRIVERS in corrente continua
LED DRIVERS constant current**0125**

LED driver
IN: 100 - 240V
OUT: 350 mA
1-6 Power LED





6 x 3,5 x 2,2 cm  4 cm

SELV 

0128

LED driver
IN: 100 - 240V
OUT: 350 mA
1-10 Power LED





11,6 x 3,4 x 2 cm  4 cm

SELV CLASS 2  

0136/15

LED driver
IN: 100 - 240V
OUT: 350 mA
1-10 Power LED




15,8 x 2,2 x 2 cm  3,2 cm

SELV  

0169/50

Multipower LED driver
IN: 220 - 240V
OUT: 350mA
min. 4 - max 22 Power LED




13 x 7,5 x 3 cm  8,5 cm

SELV 

DRIVERS DIMMERABILI in corrente continua
DIMMABLE LED DRIVERS constant current**0129 Dimmer LED**


Multipower dimmable driver
IN: 110 - 240V
OUT: 350 mA
4-15 Power LED







10,5 x 7 x 2,2 cm  7,2 cm SELV    

0129/DALI Dimmer LED


Multipower dimmable driver
IN: 110 - 240V
OUT: 350 mA
2-12 Power LED




10,5 x 7 x 2,2 cm  7,2 cm SELV   

0141/DALI

LED driver
IN: 110 - 240V
OUT: 350 mA
1-12 Power LED




11,1 x 5,2 x 2,5 cm  5,5 cm


  

0141/DIM

LED driver
IN: 110 - 240V
OUT: 350 mA
1-12 Power LED




Versione PUSH non sincronizzabile - PUSH version not synchronizable

11,1 x 5,2 x 2,5 cm  5,5 cm

0145 Dimmer LED Maxi


Multipower dimmable driver
IN: 110 - 240V
OUT: 350 mA
1- 21 Power LED



12,3 x 8 x 2,2 cm  8,4 cm SELV    

0145/DALI Dimmer LED Maxi

Multipower dimmable driver
IN: 110 - 240V
OUT: 350 mA
1- 21 Power LED




12,3 x 8 x 2,2 cm  8,4 cm SELV     

0133

Cavo di sincronizzazione per dimmer LED
Synchronization cable for LED dimmer
(art. 0129 - art. 0129/DALI - art. 0145 - art. 0145/DALI)



L 150 cm



EGOLUCE s.r.l., via I. Newton 12 - 20016 Pero - Milano
telefono +39 02 339586.1 - fax. +39 02 3535112
e-mail: info@egoluce.com - http://www.egoluce.com