






|   |   |
|---|---|
| modello:<br>model:                                  | <b>SPOON QUADRO</b>   |
| codice:<br>code:                                    | <b>6351</b>   |
| design:   | UT Egoluce  |
| anno - year:  | 2008  |
| tipologia:<br>typology:                             | <b>faretto da incasso</b><br>recessed spotlight   |
| materiali:<br>materials:                            | <b>alluminio</b><br>aluminium   |
| luce:<br>light:                                     | <b>diretta/asimmetrica</b><br>direct/asymmetric   |
| sorgente luminosa:<br>light sources:                | <b>/XW</b> LED max 1,5W 500mA 199lm 2700K<br><b>/WW</b> LED max 1,5W 500mA 210lm 3000K<br><b>/W</b> LED max 1,5W 500mA 221lm 4000K            |
| life:   | <b>&gt; 50.000 h</b>  |
| step MacAdam:                                       | <b>3</b>  |
| Indice di Resa Cromatica:<br>Color Rendering Index: | <b>&gt;80</b>   |
| grado IP - IP grade:                                | <b>40</b>   |
| peso netto - net weight:                            | <b>0,07 Kg</b>  |
| finiture:   | <b>.01 bianco</b><br><b>.02 nero</b><br><b>.45 alluminio anodizzato</b>   |
| finishes:   | <b>.01 white</b><br><b>.02 black</b><br><b>.45 anodized aluminium</b>   |
| optional:   | <b>0217</b> controcassa in materiale plastico<br>plastic box<br><br><b>0214</b> kit: box + plaster traforato<br>kit: box + perforated plaster |
| marcatatura:<br>marking:                            | <b>CE</b>   |
| simboli costruttivi:<br>symbols:                    | IP40  |

**SOLO COLLEGAMENTO IN SERIE - ONLY SERIAL CONNECTION**

#### Dimensioni - Dimensions



3,8 cm




EGOLUCE s.r.l., via I. Newton 12 - 20016 Pero - Milano  
telefono +39 02 339586.1 - fax. +39 02 3535112  
e-mail: info@egoluce.com - http://www.egoluce.com

**0214**

KIT: box + plaster traforato  
 KIT: box + perforated plaster

**0217**

Controcassa in materiale plastico  
 Plastic box





EGOLUCE s.r.l., via I. Newton 12 - 20016 Pero - Milano  
 telefono +39 02 339586.1 - fax. +39 02 3535112  
 e-mail: [info@egoluce.com](mailto:info@egoluce.com) - <http://www.egoluce.com>

La presente scheda tecnica è di proprietà di EGOLUCE srl. Tutti i diritti sono riservati. Le fotografie, le descrizioni degli apparecchi, i disegni quotati ed i valori fotometrici menzionati sono a titolo indicativo e non costituiscono alcun impegno per la nostra società che si riserva di apportare, in qualsiasi momento e senza preavviso, tutte le modifiche che riterrà opportune.

**LED DRIVERS** in corrente continua  
**LED DRIVERS** constant current
**0127**

**LED driver**  
 IN: 100 - 240V  
 OUT: 500 mA  
 1-6 Power LED





11,6 x 3,4 x 2 cm  4 cm

SELV CLASS 2  

**0169/50**

**Multipower LED driver**  
 IN: 220 - 240V  
 OUT: 500mA  
 min. 4 max 15 Power LED




13 x 7,5 x 3 cm  8,5 cm

SELV 

**DRIVERS DIMMERABILI** in corrente continua  
**DIMMABLE LED DRIVERS** constant current
**0129 Dimmer LED**


**Multipower dimmable driver**  
 IN: 110 - 240V  
 OUT: 500 mA, 1-14 Power LED






10,5 x 7 x 2,2 cm  7,2 cm SELV    

**0129/DALI Dimmer LED**


**Multipower dimmable driver**  
 IN: 110 - 240V  
 OUT: 500 mA, 2-12 Power LED



10,5 x 7 x 2,2 cm  7,2 cm SELV   

**0141/DALI**


**LED driver**  
 IN: 110 - 240V  
 OUT: 500 mA, 1-11 Power LED





11,1 x 5,2 x 2,5 cm  5,5 cm   

**0141/DIM**

**LED driver**  
 IN: 110 - 240V  
 OUT: 500 mA, 1-11 Power LED




Versione PUSH non sincronizzabile - PUSH version not synchronizable

11,1 x 5,2 x 2,5 cm  5,5 cm    

**0145 Dimmer LED Maxi**

**Multipower dimmable driver**

IN: 110 - 240V  
 OUT: 500 mA, 1-21 Power LED




12,3 x 8 x 2,2 cm  8,4 cm SELV    

**0145/DALI Dimmer LED Maxi**

**Multipower dimmable driver**

IN: 110 - 240V  
 OUT: 500 mA, 1-21 Power LED



12,3 x 8 x 2,2 cm  8,4 cm SELV     

**0133**


Cavo di sincronizzazione per dimmer LED  
 Synchronization cable for LED dimmer  
 (art. 0129 - art. 0129/DALI - art. 0145 - art. 0145/DALI)






L 150 cm

**0726/DIM**

**LED dimmer**  
 TAGLIO DI FASE (IGBT-TRIAC, TRAILING EDGE-LEADING EDGE)  
 PHASE CUT-OFF (IGBT-TRIAC, TRAILING EDGE-LEADING EDGE)  
 IN: 220 - 240V  
 OUT: 24V - 20W  
 500 mA, 1-12 Power LED



16,5 x 4,5 x 3,5 cm  5,6 cm SELV   



EGOLUCE s.r.l., via I. Newton 12 - 20016 Pero - Milano  
 telefono +39 02 339586.1 - fax. +39 02 3535112  
 e-mail: info@egoluce.com - http://www.egoluce.com